

Prevailing torque type hexagon lock nuts


low type, with polyamide insert

Tuercas hexagonales autofrenantes

forma baja con inserto de poliamida

1型非金属嵌件六角锁紧螺母

薄型，带尼龙嵌入件



d ₁	e min.	h max.	m	s	d ₁	e min.	h max.	m	s
M2,5¹⁾	5,51	3,8	2	5	M10	18,9	10	6,5	17/16*
M3	6,01	4	2,4	5,5	M12	21,1	12	8	19/18*
M4	7,66	5	2,9	7	M14	24,49	14	9,5	22,21*
M5	8,79	5	3,2	8	M16	26,75	16	10,5	24
M6	11,05	6	4	10	M20	32,95	20	14	30
M8	14,38	8	5,5	13	M24	39,55	24	15	36

1) Not included in DIN 985
No incluido en DIN 985

* Wrench size according to ISO on request
Entrecaras según ISO previa solicitud



Mechanical properties, Chemical composition, Tightening torques, etc.
Propiedades mecánicas, composición química, etc.

BN 637	○ A2	BN 1722	● A4
d ₁	☒ / ☒	d ₁	☒ / ☒
M2,5	●	M3	●
M3	●	M4	●
M4	●	M5	●
M5	●	M6	●
M6	●	M8	●
M8	●	M10	●
M10	●	M12	●
M12	●	M14	●
M14	●	M16	●
M16	●	M20	●
M20	●		
M24	●		

DIN 985
○ A2 ● A4

DIN 985: Standard withdrawn
Estándar descatálogo