


Curved spring lock washers

Arandelas helicoidales de presión

abombadas



弹性锁紧垫圈

弯曲型



~DIN 128 A



○ 1.4310
● A4

	d ₁ min.	d ₂ max.	h min.	s ¹⁾ min.		d ₁ min.	d ₂ max.	h min.	s ¹⁾ min.
M2,5	2,6	5,1	0,9	0,6	M10	10,2	18,1	2,85	2,2
M3	3,1	6,2	1,1	0,8	M12	12,2	21,1	3,35	2,5
M3,5	3,6	6,7	1,1	0,8	M14	14,2	24,1	3,9	3
M4	4,1	7,6	1,2	0,9	M16	16,2	27,4	4,5	3,5
M5	5,1	9,2	1,5	1,2	M20	20,2	33,6	5,1	4
M6	6,1	11,8	2	1,6	M24	24,5	40	6,5	5
M8	8,1	14,8	2,45	2					

1) Dimensions according to DIN 127
Dimensiones según DIN 127



Mechanical properties, Chemical composition, Tightening torques, etc.
Propiedades mecánicas, composición química, etc.


BN 674	○ 1.4310	BN 8856	● A4
	☐ / ☐		☐ / ☐
M2,5	●	M3	●
M3	●	M3,5	●
M3,5	●	M4	●
M4	●	M5	●
M5	●	M6	●
M6	●	M8	●
M8	●	M10	●
M10	●	M12	●
M12	●	M14	●
M16	●	M16	●
M20	●	M20	●
M24	●	M24	●

Curved spring lock washers

Arandelas abombadas moleteadas

弹性锁紧垫圈

弯曲型












~DIN 128 A

○ 1.4310

 M	d ₁ min.	d ₂ max.	h min.	s
M5	5,1	9,2	1,8	1,2
M6	6,1	11,8	2,4	1,6
M8	8,1	14,8	3	2
M10	10,1	18	3,4	2,2
M12	12,1	21	3,9	2,5
M16	16,1	27,3	5,5	3,5
M20	20,2	33,6	6,3	4
M24	24,5	40	6,3	5



Mechanical properties, Chemical composition, Tightening torques, etc.
Propiedades mecánicas, composición química, etc.

BN 20194			○ 1.4310					
 M			 M			 M		
M5	●	100	M10	●	100	M20	●	100
M6	●	100	M12	●	100	M24	●	50
M8	●	100	M16	●	100			